

ADD-200

WIRELESS OUTDOOR DUSK AND TEMPERATURE DETECTOR

ADD-200 detects changes of light intensity (dusk detector) and temperature (temperature detector). It is designed to work within the **ABAX 2** two-way wireless system. The detector is supported by the **ACU-220** and **ACU-280** controllers and the **ARU-200** radio signal repeater.

- dusk detector:
 - light intensity measurement in the range of 2 lx and 250 lx
 - option to select one of 16 detection thresholds
 - immunity to short and accidental changes of light intensity
- temperature detector:
 - temperature measurement in the range of -30 °C and +70 °C
 - programmable temperature threshold
- encrypted two-way radio communication in the 868 MHz (AES standard)
- transmission channel diversity – automatic selection of the one of 4 channels that will enable transmission without interference with other signals in the 868 MHz frequency band
- radio communication range in open area: up to 2000 m (with ACU-220) / up to 1600 m (with ACU-280)
- remote update of detector firmware
- remote configuration
- LED indicator
- "ECO" option for longer battery life
- battery status control
- weatherproof enclosure of high mechanical strength



TECHNICAL DATA

Battery working time (in years)	up to 2
Operating temperature range	-20 °C...+55 °C
Max. current consumption	12 mA
Weight	95 g
Maximum humidity	93±3%
Operating frequency band	868,0 ÷ 868,6 MHz
Battery	CR123A 3V
Standby current consumption	20 µA
Dimensions	58 x 115 x 34 mm
Environmental class according to EN50130-5	III
Temperature measurement accuracy	±1 °C
Warm-up period	5 s
IP code	IP65
Radio communication range (in open area) for ACU-220	up to 2000 m
Radio communication range (in open area) for ACU-280	up to 1600 m
Temperature measurement range	-20 °C...+55 °C
Light intensity measurement in range	2...250 lx



The actual appearance of the products may differ from the presented images. Product descriptions are provided in the web service for information purposes only.